

# DATA SHEET

## VIDI 250

### 4K CONFERENCING CAMERA



The Vidi 250 is a wide angle 4k camera designed for use with conferencing systems. Intended for huddle room or small to medium conferencing rooms, the Vidi 250 has a 120° field of view, allowing everyone in the room to be seen. The Vidi 250 uses auto framing technology to adjust the focus and zoom to keep participants in view. The Vidi 250 can be either display mounted or wall mounted.

#### FEATURES

- LED indications for camera activity
- Wide angle 120° Field of View
- Auto framing technology to keep participants in frame
- Electronic Pan/Tilt/Zoom with 5x zoom
- Multi-microphone array
- Display mount and wall mount options available
- Certified for Microsoft Teams and Zoom
- Covered by Biamp Systems' three-year warranty

#### ARCHITECTS & ENGINEERS SPECIFICATION

The conferencing camera shall be designed to connect with soft codec conferencing systems. The conferencing camera shall be capable of transmitting video signals of up to 1080p resolution at 30 frames per second. The conferencing camera shall have a 120° field-of-view. The conferencing camera shall include a camera with 5x zoom and electronic pan, tilt, and zoom (ePTZ). The conferencing camera shall include auto framing capabilities that adjusts the ePTZ to intelligently track users. The conferencing camera shall offer simple installation and shall be mountable on a wall or display. The conferencing camera shall be CE marked and compliant with the RoHS directive. Warranty shall be three years. The conferencing camera shall be the Vidi 250.

## VIDI 250 SPECIFICATIONS

<b>Camera and Video</b>		<b>Overall Dimensions</b>	
<b>Diagonal Field of View:</b>	120 Degrees	<b>Height:</b>	1.98 inches (50.3 mm)
<b>Horizontal Field of View:</b>	109 Degrees	<b>Width:</b>	1.97 inches (50 mm)
<b>Vertical Field of View:</b>	75 Degrees	<b>Depth:</b>	2.76 inches (70 mm)
<b>Image Sensor:</b>	12 Megapixel	<b>Weight:</b>	160g
<b>Focus Distance:</b>	174.1 cm	<b>Environmental:</b>	
<b>Lens:</b>	Up to 5x digital zoom	<b>Ambient Operating:</b>	0°C - 40°C
<b>Positioning:</b>	Autoframing capability	<b>Temperature Range:</b>	0°C - 40°C
	Electronic Pan/Tilt/Zoom	<b>Humidity:</b>	0% - 95%
<b>Camera Indicator:</b>	White/Off	<b>Altitude:</b>	10,000 ft
<b>USB Device Video Class (UVC)</b>		<b>Compliance:</b>	CE, UKCA
<b>Supported Video Resolutions:</b>	720p @ 30fps		
	1080i @ 30fps		
	1080p @ 30fps		
	2160p @ 30fps		
<b>Connections</b>			
<b>USB:</b>	USB Type C		
<b>Power:</b>	USB Type C		

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

## OPTIONAL ACCESSORIES



**VMA 200-DM**  
Side Display Mount



**VMA 200-WM**  
Wall Mount

Biamp is either a trademark or registered trademark of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.