

EASYCONNECT MPX 250

BYOM COLLABORATION SWITCHER



EasyConnect MPX 250 is an innovative BYOM collaboration switcher with integrated charging, cable management and control of the meeting room equipment.

Simply plug in the USB-C cable to your device and press a button to start sharing, get internet access, and take control of room equipment such as camera, speakers and microphones. Enjoy meetings with reliable connection, fully powered laptops and a clutter free table.

Bright and vivid colors guide you during the meeting. In combination with the touch controller it allows the connected participant to control and switch who is sharing their screen and has control of the connected in-room equipment such as cameras, microphones and speakers.



Idle



Charging



Sharing



HDMI Ingest

The BYOM collaboration switcher shall be designed with a touch panel to control screen sharing. The BYOM collaboration switcher shall allow meeting participants to control and switch who is sharing their screen. The BYOM collaboration switcher shall have a touch control. The BYOM collaboration switcher shall indicate screen sharing with LED indicators on the touch display. The BYOM collaboration switcher shall include four USB-C cables for connections to laptops and mobile devices. The BYOM collaboration switcher shall include cable management with retractable USB-C cables. The BYOM collaboration switcher shall charge connected devices up to 100W. The BYOM collaboration switcher shall support dual video output and network sharing. The BYOM collaboration switcher shall be CE marked and compliant with the RoHS directive. Warranty shall be three years. The BYOM collaboration switcher shall be the EasyConnect MPX 250.

EasyConnect MPX 250 gives you a smooth and seamless setup for all your meetings. No matter what video conferencing platform the experience will be hassle free, with the benefit of increased productivity. Connect to any of the most popular video conference platforms such as Microsoft Teams, Zoom and Google Meet. It is also possible to connect to other wireless screen sharing systems for a hybrid setup.



Dual Screen Support

Enhanced connectivity with dual video output



Shared Internet Connection

Network connectivity through USB-C



Charge your devices

Connected devices are charged with up to 100W.



Cable Management

Retractable USB-C cables with integrated retention mechanism



Plug and play

No software installation needed.

Easily share your screen and audio in a meeting with full control of room equipment such as camera, speakers and microphones. All with the touch of your fingertip.



| | | | |
|--|--|---------------------------------|---|
| Connectivity & Ports | | Installation | Pre-mounted table installation with integrated retractable system |
| USB-C Input Ports | 4 x USB Type-C 3.2 Gen 2, up to 10 Gbps, DP Alt Mode 1.2-1.4, up to 100W | Supported Configurations | |
| USB-C Downstream Ports | 2 x USB 3.2 Gen 2, up to 10 Gbps, 5V / 3A, Power Delivery 3.0 | BYOD/BYOM Setup | Full bring-your-own-device/meeting support |
| USB-A Ports | 2 x USB 3.2 Gen 2, up to 10 Gbps, 5V / 0.9A | UC Integration | Microsoft Teams, Zoom, Google Meet |
| HDMI Output | HDMI 2.1, max resolution 8K @ 60Hz HDCP v2.3, FRL mode | Dual Display | Video extension and dual output support via MST hub (Windows: extended, macOS: mirrored) |
| Network RJ45 Port 1: | 10/100 Mbps Ethernet (Management) | Mode Switching | Long press switching between HDMI-ingest (MTR) and BYOM modes |
| RJ45 Port 2: | 10/100/1000 Mbps Ethernet (Internet Sharing) | Environmental | |
| Wi-Fi | 2.4 GHz Wi-Fi for MPX 250 Management Console | Temperature Range: | 5°–40° C |
| Extension Port USB-C Extension Port: | DP Alt Mode 1.4, up to 4 x 8.1 Gbps, video output | Humidity: | 5%–80 % |
| DC IN | 20V / 10A power supply input | Compliance: | CE, FCC, ETL, RoHS, REACH |
| Touch Controller & Cable Management | | | |
| Cable Length | 4 x 2-meter retractable USB-C cables | | |
| Cable Extension | Up to 80 cm above tabletop Integrated guide rails | | |
| Touch Interface | Capacitive touch buttons for each port with LED status indicators | | |
| Status Indicators | Visual LED indicators (idle, connected, sharing, BYOM mode) | | |



- MPX 250 Table Connection box with touch controller and mounting brackets for under-table installation
- Power adapter with 1-meter AC cord
- Mounting system with retractable cable management
- 4x USB-C cables with cable weights
- Management console software (PC & Mac)



MPX 250 DC
MPX Direct Connection Hub



MPX 250 EXT 30
Wall Side Extension Kit

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice. Biamp and EasyConnect MPX 250 are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.



A: 9300 S.W. Gemini Drive Beaverton, OR 97008 USA

T: +1 503.641.7287

W: www.biamp.com